

**OFFICE OF THE ADDITIONAL DIRECTOR GENERAL OF POLICE, CID,
ASSAM, ULUBARI, GUWAHATI.**

NOTICE INVITING TENDER

NIT No. E/VII/111-14/CID/3440-42

Dated Guwahati, the 28th July 2017 .

Sealed tender on plain papers **affixing (in Technical Bid) non refundable court fee stamps of Rs.8.25 (Rupees eight and Paise twenty five only)** is invited for Supply of various equipments for Narcotic cell of CID as per Technical specifications enclosed herewith as **Annexure.**

Terms & condition:

1. The tender addressed to the Addl. Director General of Police (CID), Assam, B.K. Kakoti Road, Ulubari, Guwahati, – 781007 must reach the undersigned up to **2 : 00 P.M.** on **24/08/2017** . No tender received thereafter will be accepted and the undersigned shall not be responsible for any delay in submission of tender. All tenders received after the due date & time shall be returned to the respective Vendor without opening the same. Intending Vendors shall submit tenders in the box kept in front of the office chamber of Addl. Director General of Police (CID), Assam, Ulubari, Guwahati. The tender Box will be opened on the same day at **3.30 PM** or on subsequent working day at **11.30 AM** if it falls on Govt. holiday in presence of Vendors or their authorized representative present at that time.

Tenders can also be submitted by post but the Deptt. shall not be liable for any postal delays. No Tender will be accepted after the due date and time.

2. Intending vendors may collect tender paper / documents on payment of Rs.500/- (Rupees five hundred) only through uncrossed IPO / BANK DRAFT payable in favour of the undersigned on any working day during office hours up to **22/08/2017** . They may also download the NIT from the Assam Police website www.assampolice.gov.in or www.tenders.gov.in. In that case the vendor will have to deposit the cost of tender documents through uncrossed IPO / Bank draft at the time of submission of tender.

3. Vendors shall submit BIDS in two parts in separate sealed envelopes i.e. **TECHNICAL BID** and **PRICE BID**. Both these bids shall further be put in an envelope before putting in tender box, duly sealed. The vendors shall also superscribe on the individual envelope. The document written on **CD in PDF format must be enclosed inside the envelope.** The document must be written on CD after signing the documents and should be same as the hardcopy submitted.

4. All papers submitted by Vendor should be serially numbered and signed. An index of documents submitted giving page number should also be submitted by the Vendor under his signature.

5. **Validity:** Bids must be valid for acceptance for a minimum period of 365 (three hundred sixty five) days from the bid closing date.

6. **Earnest Money deposit (EMD)**

(i) Earnest Money of Rs.50,000/- in the Form of NSC / FDR of Bank / Irrevocable Bank Guarantee with **validity for at least 12 (twelve) months** in the name of the Proprietor / Partner or shareholder of the firm concerned duly pledged in favour of the undersigned. Earnest Money will be released after finalization of Tender. Earnest money deposited with the tender shall bear no interest. The Earnest Money will be liable to be forfeited, if the vendor withdraws or amends

or impairs or derogates from the tender in any respect within the period of validity. Bids received without EMD will summarily be rejected.

(ii) Any vendor who has claimed exemption of Earnest Money Deposit and Security deposit shall furnish a certified copy of such order indicating therein clearly that they are exempted.

7. **Bid Evolution criteria :**

Bids conforming to the terms and conditions stipulated in the bid document subject to qualifying the Bid Selection Criteria will be considered for further evaluation.

8. **Bid selection Criteria :**

- (i) Court fees stamp
- (ii) Tender Fee
- (iii) Earnest Money Deposit amount.
- (iv) Proof of dealership from the Original Equipment Manufacturer (OEM) or his authorised agent in India. In case of submission of bids by OEM itself, then sufficient proof / self declaration has to be enclosed.
- (v) An **Affidavit** stating that neither the vendor , principal supplier of equipment (hardware, software and accessories) or any associated / affiliated company is blacklisted by any Public Sector Undertaking / agency of the Govt. of India/ State Govt.

Vendor failed to fulfill the above criteria will be out rightly rejected for further evaluation and will be considered as non responsive.

Vendors fulfilling the above criteria will be considered for technical evaluation. The vendor will be considered for technical evaluation along with agreement to terms and condition and submission of relevant documents fulfilling the eligibility criteria for further evaluation by purchaser.

9. **Other Information / Documents :**

All Vendors must submit relevant documents to support their eligibility criteria along with the following documents (in Technical Bid) complete in all respect and duly self attested.

- (i) Audited Financial Statement for the last two years i.e. 2012-13 & 2013-14 (up to 31-03-2014) certified by Chartered Accountant.
- (ii) Permanent Account Number.
- (iii) GST Registration Certificate.
- (iv) Income Tax Return for last two years i.e 2015-16 & 2016-17.
(up to 31-03-2017)
- (v) Passport size photograph of the authorized signatory.
- (vi) Bank Account No. with name of Bank, type of account, Bank address..
- (vii) All other supporting documents as required for technical evaluation in the tender.

10. The short listed Vendors will have to arrange for the Technical and / or Field / practical demonstration of the Equipment at their own cost at the place and date to be fixed by the authority. The bids of the firms / vendors who do not arrange / participate in the demonstration as above will be treated as rejected.

11. Commercial bids of only those vendors will be opened who will be **technically qualified**.

12. Vendors should furnish detailed Technical Specifications of the product along with **MAKE, MODEL, MANUFACTURERS CATALOGUE / LEAFLET** as well as sub-assemblies, if any and clearly indicating the Warranty period and provision of annual Maintenance Contract (**both soft and hard copy**). Vendor will specify after sales service and

support mechanism clearly in the Bid. Frequency of routine maintenance during warranty period and break down maintenance should also be clearly specified.

13. The specifications laid down in the NIT are the minimum configuration of the systems / items. Systems / items of better / higher configuration or better technology may be quoted for consideration.

14. Vendors quoting Rates as Authorised Dealer / Authorised Distributor etc. must submit authority letter for the item (s) quoted from their manufacturers.

15. Tender should be clearly typed or written and the rates (net) should be written both in figure and words. There should not be any over writing, erasure in the rates. In case of over writing or erasure or any such alteration, the item shall be rejected outright.

16. Failure to fulfill the terms and conditions of the tender notice may lead to rejection of the bid without any reference to the Vendor and no correspondence will be entertained in this regard.

17. **CORRECTION OF Error:** Vendors are advised to exercise adequate care in quoting the prices. No excuse for corrections in the quoted figures will be entertained after the commercial proposals are received by CID Assam. Arithmetic errors in proposals will be corrected as follows: In case of discrepancy between the amounts mentioned in figures and in words, the amount in words shall govern. The amount stated in the proposal from, adjusted in accordance with the above procedure, shall be considered as binding, unless it causes the overall proposal price to rise, in which case the proposal price shall govern.

18. The rates once quoted will be final and no request for change/ alteration thereof will be entertained thereafter. The rates should be quoted F.O.R. destination as stated in 1st para of the NIT and should be inclusive of packing, transportation, all accessories and other ancillary expenses. GST should be shown separately.

19. Rates quoted should be valid for 1 (one) year with effect from the date of submission of bid with a provision for further extension of finally approved. The rates to be quoted in Indian currency and payment shall be made to successful vendors in Indian currency.

20. Once the rates offered in the quotation are accepted, no enhancement will be entertained at any circumstances and Vendors will be liable to supply the items at the rate accepted by the CID, Assam Police. Failure to supply the items at the accepted rates will entail the offer being cancelled and the security Money will be forfeited to the Govt. of Assam.

21. For imported items rates should be indicated separately i.e. rates with Custom duty and rates without Custom Duty.

22. All pages of the tender document together with terms and conditions and the documents enclosed with the tender shall be signed by the authorized signatory. Acceptances signing of the Notice Inviting Tender and the detailed terms and conditions in the format of certificate enclosed shall be deemed as the final acceptance of these terms and conditions.

23. Tenders accompanied by all required documents be submitted under sealed cover and distinctly and conspicuously marked as "Supply of various equipments for Narcotic cell of CID, Assam". The outer and inner envelopes mentioned above shall indicate the name and address of the vendor/agency. Failure to mention the address on the outside of the envelope could cause a proposal to be misdirected or to be received at the required destination after the deadline.

24. Modification and Withdrawal of Proposals :

No proposal may be withdrawn in the interval between the deadline for submission of proposals and the expiration of the validity period specified by their bid during the validity period.

25. (a) The approved suppliers will have to execute the orders of supply within the time frame specified in the supply order.

26. **Inspection:** The inspection parameters shall cover the following:

Inspection of goods on receipt at consignee's / user's site: The designated officer / Committee authorized by purchaser will do the inspection for sample checking to ensure that the delivered goods are same which was quoted in the bid. Any deviation to the bid proposal with the delivered items will be rejected and Vendor will supply the proposed items afresh with own cost and any delay for timeline will be calculated as per SLA violation penalty.

27. The earnest Money of the unsuccessful Vendors will be released to them after finalization of the tenders.

28. The Addl. Director General of Police, CID , Assam reserves the right not to place any order even after execution / acceptance of the formal contract agreement and for which no claim or compensation whatsoever will be entertained.

29. The Director General of Police, Assam may rescind forthwith the contract in writing if:

(a) A contractor assigns or lets any contract in respect of any other contract entered into with the Government.

(b) Vendor or his agent or servants are found guilty of fraud of this contract or any other contract.

(c) Declines, neglect or delays to comply with demand / requisition or in any other way fails to perform or observe any condition of or all conditions of the Contract agreement.

(d) The Vendor having been Blacklisted or debarred by any Govt./ Semi-Govt. organizations on previous occasions for indulging in illegal, unethical, corrupt etc. practices.

30. If the successful Vendor willfully neglects, fails to perform or observe any or all conditions of the contract agreement or attempts to cheat or indulge in foul practices, the Addl. Director General of Police, (CID) Assam impose a ban upon such Vendor (s) for future business within the Department.

31. In case any manufacturing defect in the articles supplied is detected or any damages to the equipment during transit/handling before final acceptance by the department, the Addl. Director General of Police, (CID) Assam will be at the liberty to return the stores at the expense of the suppliers who in turn will replace the stores without any financial liability to the department. Else the security deposit will be forfeited to the Govt.

32. The security deposit (**EMD**) will be returned to the selected vendor after signing the agreement and submission of performance bank Guarantee (PBG) for the duration of contract.

33. **No ADVANCE PAYMENT** will be made to the approved supplier.

34. Performance security @ 5% of the total value of supply order has to be deposited by the supplier in the form of NSC/FDR of Bank/ Irrevocable Performance Bank Guarantee in favour of Addl. Director General of Police (CID), Assam at the time of signing of Deed of Agreement to ensure satisfactory performance of the items supplied with validity for a period of 5 (five) years from the date of acceptance of product. This deposit will be released in due course after the expiry of specified period. Performance Security will not accrue any interest.

35. It will be imperative on the part of the supplier to fully associate the representatives of the purchaser in the maintenance of the system.

36. The vendor must obtain certificate/declaration from Original Equipment manufacturer confirming that the availability of spare, service and support for the system to be guaranteed by them for a minimum period of 10 (ten) years from the date of agreement.

37. In case the successful Vendor (s) is found to have been involved in breach of any condition (s) at any stage during the warranty / guaranty period the legal action as per rules / laws shall be initiated against him/them. In that case, Security Deposits will be forfeited, besides debarring / Black listing the Vendor for at least 5 years from any further dealing with Assam Govt./ Police.

38. Goods accepted by the Purchaser at initial inspection and in final inspection in terms of the contract shall in no way dilute purchaser's right to reject the same later, if found deficient in terms of the quality.

39. Liquidated Damages:

In the event of the Vendor's failure to submit the Guarantees and Documents and supply the materials as per schedule specified in this NIT, CID, Assam Police may at its discretion withhold any payment until the completion of the contract. It may also deduct from the Vendor as agreed, liquidated damages to the sum of 0.5% of the contract price of the delayed services, material delivery as per timeline (as detailed in this NIT) for every week of delay or part of a week, subject to the maximum value of the Liquidated Damages being not more than 10% of the value of delayed services. This right to claim any liquidated damages shall be without prejudice to other rights and remedies available to CID, Assam Police under the contract and law.

40. Risk of transportation will be borne by the Vendor themselves

41. Payment Milestone:

Implementation Phase:

- a) 90% after successful Delivery, installation & commissioning and final acceptance of stores.
- b) 10% after completion of 1(one) year warranty.

42. All the legal proceedings arising out of any dispute between the parties shall be settled within the territorial; jurisdiction of the Courts in Guwahati.

Sd/-

Superintendent of Police, CID,
Assam, Ulubari, Guwahati.

Memo No. E/VII/111-14/CID/3440-42

Dated Guwahati, the 28th July 2017

As directed, copy forwarded to:

1. The Addl. Director General of Police (M & L), Assam, Guwahati for favour of kind information.
2. The Addl. Superintendent of Police (C), Assam Police HQ, Ulubari, Guwahati for information and necessary action. He is requested to upload the NIT in the official website of Assam Police www.assampolice.gov.in and the Indian Government Tenders Information System www.tenders.gov.in .
3. The C.P.R.O, Assam Police Headquarters, Guwahati for information and necessary action. He is requested to give wide publicity of the NIT by publishing the caption of the NIT in two National Daily Newspapers and two Local Daily Newspapers and to furnish to the undersigned paper cuttings of the published NIT.
4. The Office Notice Board.

Sd/-

Superintendent of Police, CID,
Assam, Ulubari, Guwahati

ANNEXURE

1) NIGHT VISION

TECHNICAL SPECIFICATIONS

Magnification X	: 6 X (minimum)
Field of View, deg	: 8°
Focus range, m	: 25-∞
Inter-papillary distance	: 55-71 (with manual adjustment)
SMART Technology	: yes

IMAGE INTENSIFIER TUBE

Type	: Gen-III
Resolution, lp/mm	: 64-72 lp/mm (min)
Total Dark IR system	: yes

POWER

Power supply	: 2 x 3 V CR123A type battery Two AA size 1.5-V alkaline or Li-Ion Rechargeable
Battery life	: 50 hrs
Indication (inside field of view)	: “IR-on” and low-voltage indicators

MECHANICAL

Weight, (include batteries)	: 1100 grams.
Dimensions, mm	: 305x150x90
Operating Temp., °C	: -30 to +70

DETECTION RANGE

Human Target	: 600 m
Vehicle Target	: 1,300 m

(Under star-light condition, no-moon)

2) 5 KVA ONLINE UPS

TECHNICAL SPECIFICATIONS

INPUT

Phase	: Single
Voltage Range	: 160V-280V

Power Factor	: 0.99
Frequency	: 45Hz-55Hz
OUTPUT	
Voltage/Regulation	: 220/230/240V \pm 1%
Full Load Current	: Rated at 0.9P.F
Nominal Frequency	: 50Hz \pm 0.5Hz
Power Factor	: 0.9 P.F
Overload	: 125 % for 10 minutes & 150% for 1 minute
Static Voltage Regulation	: \pm 6% for 50% step load change
Total Harmonic Distortion	: < 3% for Linear < 5% for Non Linear load
Crest Factor	: 4:1

PROTECTIONS

Charger	: Input circuit braker, Charger over voltage, Charger over current limit
Battery	: Battery low cut off/Current limit, HRC fuse in battery path, Battery over charger trip
Inverter	: Output over voltage/Over load trip, Current limit, Short circuit

DISPLAY

Indications	: Main on, UPS On, UPS Trip, UPS OV/UV, Battery Low Trip,
Display	: LCD Display for checking Input and Output Parameters

ENVIRONMENT

Operating Temperature Range	: 0° C to 55° C
Relative Humidity	: 95% Non condensing
Maximum Operating Altitude without Derating	: 3000 meters
Acoustic Noise	: < 55db at 1metre distance

3) FAX

TECHNICAL SPECIFICATIONS

- Standard : G3
- Scan line density : 8x3.85/mm, 8x7.7/mm, 8x15.4/mm

- Transmission time : G3: 3 seconds
- Data compression method: MH, MR, MMR, JNIG
- Maximum scan size : A4 (210x297mm)/Legal (8 ½ x 14)
- Print process : Printing on standard paper using GelSprinter
- Transmission speed G3 : 33.6 k-2400 bps (auto shift down system) Internet Fax
Transmission and reception
- Network : LAN local Area Network
- Ethernet : 10 BASE-T/100 BASE-T
- Transmit Function : Email
- Scan line density : 8x3.85/mm, 8x77/mm, 8x15.4/mm
- Maximum scan size : A4 (210x297mm)/Legal (8 ½ x 14)
- Communication Protocols
 - Transmission : SMTYP, TCP/IP
 - Reception : POP3, SMTP, TCP/IP
- E-mail format : Single/multi-part, MIME Conversion
- Attached file form : TIFF-F (MH, MR, MMR compression)
- Internet communication : Send and receive e-mail with a computer that has an e-mail address
- Authentication method : SMTP-AUTH, POP before SMTP
 - E-mail send functions : Automatic conversion of sent documents to e-mail format and e-mail transmission. Memory transmission only.
- E-mail receive functions : Automatic detection and printing of appended TIFF-F (MH) files and ASCII text. Memory reception only.

4) MULTIMEDIA PROJECTOR

TECHNICAL SPECIFICATIONS

Power supply		100-240 V AC, 50/60 Hz
Power consumption		100-120 V: 310 W, 220-240 V AC: 290 W (0.4 W when Standby mode set to ECO*1, 5 W when Standby mode set to Network, 14 W when Standby mode set to Normal)
LCD panel	Panel size	16.0 mm (0.63 in) diagonal (4:3 aspect ratio)
	Display method	Transparent LCD panel (x 3, R/G/B)
	Pixels	786,432 (1024 x 768) pixels
Lens		Manual zoom (1.6x) (throw ratio: 1.2-1.9:1), manual focus, F 1.60-2.12, f 15.30-24.64 mm

Lamp	Lamp	230 W x 1 lamp (240 W driven)
	Lamp replacement cycle	10,000 h (lamp power: Normal/Eco)
Center-to-corner uniformity*2		85%
Contrast*2		10,000:1 (Full On/Off) (input signals: PC, lamp power: Normal, picture mode: Dynamic, IRIS: On)
Scanning frequency	HDMI IN	fH: 15-80 kHz, fV: 50-85 Hz, dot clock: 162 MHz or lower
	RGB	fH: 15-100 kHz, fV: 50-100 Hz, dot clock: 162 MHz or lower (Signals exceeding the dot clock rate of 140 MHz are downsampled.)
Optical axis shift		9:1 (fixed)
Keystone correction range	Vertical	±40 ° (±30 ° when using Easy Setting) (maximum value of XGA input)
	Horizontal	±30 ° (±20 ° when using Easy Setting) (maximum value of XGA input)
Installation		Ceiling/floor, front/rear
Terminals	VIDEO IN	Pin jack x 1 (Composite VIDEO)
	LAN	RJ-45 x 1 (for network connection, 10BASE-T/100BASE-TX, compliant with PLink™)
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	USB-Type A	for Memory Viewer x 1
	USB-Type B	for USB Display x 1
Built-in speaker		4.0 cm (1-9/16 in) round shape x 1, output power: 10.0 W (monaural)
Operation noise*2		37 dB (lamp power: Normal), 29 dB (lamp power: Eco)
Dimensions (W x H x D)		352 x 98*4 x 279.4*5 mm (13-27/32 x 3-27/32*4 x 11*5 in)
Weight*6		Approx. 3.4 kg (7.5 lbs)
Operating temperature		0-40 °C [32-104 °F] (less than 1,400 m [4,593 ft] above sea level, HIGH ALTITUDE MODE: OFF)
Operating humidity		10-80 % (no condensation)
Wireless	Standard	2.4 GHz: IEEE802.11b/g/n, 5.0 GHz: IEEE802.11a/n

Accessories Wireless remote control unit × 1, power cord × 2, batteries for remote control (R03/LR03/AAA type battery × 2), RGB signal cable × 1, lens cap × 1.

Software CD-ROM (Logo Transfer Software, Multi Projector Monitoring & Control Software, Wireless Manager ME 6.3)

5) SEARCH LIGHT

TECHNICAL SPECIFICATIONS

Dimensions	: 160mm dia x 250 mm length fitted with specially designed deep parabola reflector
Lamp	: 50/55 watt, 12 volts halogen lamp
Power	: 12 volts & 7AH rechargeable maintenance free battery. Suitable for 35w / 55w Halogen Lamp.
Operating range	: of about 1000 mt. (i.e. 1 KM)
Beam distance	: of 350 mt. So as to detect group of persons .
Front glass	: Shock resistance front glass.
Charger	: SMPS inbuilt charger working on from 90v to 270v, 50Hz.
Emergency	: Lighting Effect for INDOORS user.
Modes	: Timer, Manual Flasher and Continuous Mode.
Indicators	: DC blown fuse indicator is provided on the panel. : Advance low battery status indicator is also provided.

6) DIGITAL VIDEO CAMERA

TECHNICAL SPECIFICATIONS

SENSOR

SENSOR TYPE : 1/ 5.8 type (3.1 mm) back-illuminated Exmor R® CMOS Sensor

EFFECTIVE PIXELS (VIDEO) : approx. 2.29 Megapixels (16:9)2

EFFECTIVE PIXELS (STILL IMAGE): approx. 2.29 Megapixels (16:9)/approx. 1.71 Megapixels (4:3)

PROCESSOR

IMAGE PROCESSOR : BIONZ X™ image processor

LENS

LENS TYPE : ZEISS® Vario-Tessar®

LENS COVER : Manual

APERTURE : F1.8-F4.0

FOCAL DISTANCE : f = 1.9-57.0 mm
FOCAL LENGTH (35 MM EQUIVALENT) (VIDEO) : f=26.8–804.0 mm (16:9)
FOCAL LENGTH (35MM EQUIVALENT) (STILL IMAGE): f=26.8–804.0 mm (16:9),
f=32.8–984.0 mm (4:3)
MINIMUM FOCUS DISTANCE : approx. 1 cm (Wide), approx. 80 cm (Tele), approx. 0.40
(Wide), approx. 31.5 (Tele)

ZOOM

OPTICAL ZOOM : 30x

LCD

SCREEN TYPE : 6.7 cm (2.7 type) Clear Photo LCD display
(230 400 dots) Wide (16:9)

IMAGE STABILIZATION

IMAGE STABILIZATION TYPE : Optical SteadyShot™ image stabilisation w/
Intelligent Active mode (Wide to Tele)

FOCUS

FOCUS TYPE : Contrast AF
FOCUS MODE : Auto/Manual (Menu)
FOCUS AREA : Full range Focus

EXPOSURE

LOW LUX MODE : Yes
AUTO IRIS CONTROL : F1.8 - F10
BACKLIGHT COMPENSATION : Yes (Auto)
GAIN CONTROL : Auto
MINIMUM ILLUMINATION : Standard: 6 lux (1/25 Shutter Speed), Low Lux:
3 lux (1/25 Shutter Speed)

SHUTTER SPEED

AUTO CONTROL RANGE : 1/6–1/10000
STANDARD : 1/25–1/10000
MANUAL IRIS CONTROL(PHOTO MODE) : 1/25–1/10000

STORAGE MEDIA

MEDIA TYPE : XAVC S HD: Micro SDXC Memory Card (Class 10 or Higher),
AVCHD, Still : Memory Stick Micro™ (Mark 2), Micro SD/SDHC/SDXC Memory
Card (Class 4 or Higher)

RECORDING

RECORDING FORMAT (VIDEO) : AVCHD format ver. 2.0 compatible: MPEG4-AVC/H.264, MP4: MPEG-4 AVC/H.264, XAVC S format MPEG4-AVC/H264

RECORDING FORMAT (STILL IMAGE): JPEG (DCF Ver. 2.0, Exif Ver. 2.3, MPF Baseline-compliant)

AUDIO

MICROPHONE : Built-in Zoom Microphone

AUDIO RECORDING FORMAT : Dolby Digital 2ch Stereo, Dolby Digital Stereo Creator10, MPEG-4 AAC-LC 2ch11, MPEG-4 Linear PCM 2ch (48 kHz/16 bit)12

ADVANCED FEATURE

SCENE SELECTION: Auto / Night Scene / Sunrise & Sunset / Fireworks /Landscape / Portrait / Spotlight / Beach / Snow

PLAYBACK

HIGHLIGHT MOVIE MAKER : Yes 10, Highlight BGM (Pre-installed 6 music files, Music transfer compatible)13

MOTION SHOT VIDEO : Yes

PROJECTOR

LIGHT OUTPUT : Up to 13 lumen

PROJECTED IMAGE SIZE : 10 type - 100 type

ENDURANCE (BATTERY LIFE) : approx. 1h10min(Supplied Battery)

WIRELESS FUNCTION

WI-FI® : Yes (Wi-Fi Compatible, IEEE 802.11b/g/n (2.4 GHz band))15

POWER

BATTERY TYPE : NP-BX1

CHARGE ON CAMCORDER (CHARGING: Yes (approx. 2 h 35 min)19

TIME WITH SUPPLIED BATTERY)

USB CHARGING : DC 5 V 800 mA

SIZE & WEIGHT

DIMENSIONS (W X H X D) : approx. 59.0 mm (W) × 59.5 mm (H) × 128.0

(INCLUDING SUPPLIED BATTERY) mm (D)2021, approx. 2.38 (W) × 2.38 (H) × 5.13 (D)2021

WEIGHT (MAIN UNIT ONLY) : approx. 210 g, approx. 7.4 oz

WEIGHT (INCLUDING SUPPLIED BATTERY) : approx. 235 g (NP-BX1)22, approx. 8.3 oz (NP-BX1)22

ACCESSORIES: Rechargeable Battery Pack(NP-BX1) (1)23, AC Adaptor (1)23, USB Connection Support Cable (1)23, HDMI (micro) Cable (1)23, Operating Guide (1)23

7) DIGITAL STILL CAMERA

TECHNICAL SPECIFICATIONS

Sensor

SENSOR TYPE : 1/2.3 type (7.76 mm) Super HAD CCD™

NUMBER OF PIXELS (EFFECTIVE) : Approx. 20.1 Megapixels

LENS

LENS TYPE : Vario-Tessar 8 elements in 7 groups(including 5 aspheric elements)

F-NUMBER (MAXIMUM APERTURE): F3.3 (W) – 6.3 (T)

FOCAL LENGTH : f=4.5-36mm

FOCUS RANGE : iAuto:AF(W:approx. .5cm(0.16 ft.) to infinity,
(FROM THE FRONT OF THE LENS) T: approx. 150cm(4.92 ft.) to infinity), Program Auto:AF(W:approx. .5cm(0.16 ft.) to infinity, T: approx. 150cm(4.92 ft.) to infinity)

OPTICAL ZOOM : 8x(Optical Zoom during movie recording)

DIGITAL ZOOM (STILL IMAGE) : Up to 64x (VGA)

DIGITAL ZOOM (MOVIE) : Precision Digital Zoom Approx. 32x

FOCAL LENGTH (F=)

35MM FORMAT EQUIVALENT : Still images: 4:3: f=26-130mm, 16:9: f=28-224mm, Movies: 16:9: f=28-224mm (SteadyShot Standard), f=28-314mm (SteadyShot Active), 4:3: f=34-272mm (SteadyShot Standard), f=34-381mm (SteadyShot Active)

LCD

SCREEN TYPE: 6.7cm(2.7-type)(4:3) / 230,400 dots / ClearPhoto / TFT LCD

8) CAMERA

STEADYSHOT : Still images: Optical, Movies: Active Mode, Optical type with electronic compensation
EXPOSURE COMPENSATION : +/- 2.0 EV, 1/3 EV step
SHUTTER SPEED : iAuto (2 - 1/1, 600), Programme Auto (1 - 1/1, 600) (*3)
CONTINUOUS SHOOTING SPEED (MAXIMUM) (WITH MAX.
SELF-TIMER : Off , 10sec., 2sec., portrait1, portrait2
MINIMUM ILLUMINATION : Auto: 22.0 lux (Shutter Speed 1/30)

FLASH

FLASH MODE : Auto, Flash On, Slow Synchro, Flash Off, Advanced Flash
FLASH RANGE : ISO Auto: approx. 0.3m to 2.8m (W), approx. 1.5m to 2 m (T), ISO3200: up to approx. 5.3m (W), approx. 3.3m (T)

RECORDING

RECORDING FORMAT : Still images: JPEG, Movie: MP4
MOVIE RESOLUTION : MP4: 9 M Fine (1,280 x 720/30fps), 6 M STD (1,280 x 720/30fps), 3 M VGA (640 x 480/30fps)
INTERNAL MEMORY : Approx. 27 MB

INTERFACE

INPUT AND OUTPUT TERMINALS : Multi (AV/USB), Hi-Speed USB (USB2.0)
WI-FI® CONNECTIVITY

POWER

POWER SOURCE : DC3.6V (supplied battery)/DC5.0V (supplied AC adaptor)
BATTERY SYSTEM : Rechargeable Battery Pack NP-BN
POWER CONSUMPTION (CAMERA MODE) : Approx. 1.2W

OTHERS

DIMENSIONS (W X H X D) (CIPA) : Approx. 93.1 x 52.5 x 22.5 mm
WEIGHT (CIPA) : Approx. 104 g (Body only), Approx. 120 g (With battery and media)

ACCESSORIES : Rechargeable Battery Pack NP-BN*11, Multi USB cable, Wrist Strap, Instruction Manual, AC Power Code

9) INTERACTIVE SMART WHITEBOARD

TECHNICAL SPECIFICATIONS

Size	: 78” diagonal LxH - (6x4 feet)
Whiteboard Surface	: Ceramic High luminance nanotechnology, anti-scratch, anti glare surface
Aspect Ratio	: 4:3
Touch Technology	: DVT (Digital Vision Touch) Optical Sensors
Touch type	: Finger touch & touch with any opaque object
Multi-touch capability	: Yes
Touch accuracy	: 0.1 mm
Touch response time	: < 8ms
Resolution	: 9600 x 9600
DPI	: 600
Power supply	: USB (<5V/500mA)
Operations Temperature	: 0 to 60 degree Celsius; Humidity: 0% to 95%
Operating system Windows	: XP/2003/Vista/7/10, Linux, Android, MAC 10.6/10.7
Min. system configuration	: Intel PIV or above processor, 512MB RAM, 1GB free disk space, one projector (short throw projector recommended for best experience)
Accessories	: Smart Whiteboard Software, USB Cable, Smart Pens, Wall mount bracket.

10) PHOTOCOPIER

TECHNICAL SPECIFICATIONS

Engine speed (max)	: 20ppm
Paper size	: Max A3 (11” x 17”).min. A6 (5 ½ “ x 8 ½”)
Paper capacity	: Max 1850 sheets
First copy time	: 6.4 seconds for A4 (6.5 seconds for 8½” x 11”)
Memory	: Std 64 MB.Max 192 MB

COPIER

Continuous copy : Max.999 copies

Resolution : 600 x 0600dpi

PRINTER

Interface : USB 2.0

Resolution : 600 x 600dpi

COLOUR SCANNER

File Formats : TIFF, PDF, JPEG, BMP

11) DESKTOP COMPUTER

TECHNICAL SPECIFICATIONS

System Features

- Cache Memory : 2 MB
- Processor Name : Pentium Quad Core
- Processor Brand : Intel
- Processor Frequency : 1.6 GHz with Turbo Boost Upto 2.64 GHz
- Operating System : Free DOS
- Processor Model : J3710

Memory

- Memory Speed : 1600 MT/s
- Memory Slots : 1 x DDR3 Slot
- System Memory : 4 GB DDR3
- Memory Detail : 1 x 4 GB

Display

- HD : Yes

Graphics

- Integrated Graphic Processor : Intel HD Graphics

Webcam

- Built-in Webcam : Yes

Storage

- Storage Interface : SATA
- Hard Drive : 1 TB

12) DESKJET PRINTER

TECHNICAL SPECIFICATIONS

GENERAL	
Print technology	HP Thermal Inkjet
Duty cycle (monthly, letter)	Up to 1000 pages
Duty cycle (monthly, A4)	Up to 1000 pages
Print speed black (normal, letter)	Up to 7.5 ppm
Print speed black (normal, A4)	Up to 7.5 ppm
SCAN	
Scan resolution, optical	Up to 1200 dpi
Bit depth	24-bit
Scan technology	Contact Image Sensor (CIS)
COPY	
PAPER HANDLING	
Paper trays, standard	1
PAPER MEDIA	
Media weight, recommended	75 g/m ²
MACHINE DIMENSIONS & WEIGHT	
Package weight	4.48 kg
CABLE INCLUDED	

Accessories	Yes, 1 USB 1.5 m Cable
ENVIRONMENTAL	
Operating temperature range	5 to 40°C
Operating humidity range	15 to 80% RH (non-condensing)

13) COMPUTER TABLE

TECHNICAL SPECIFICATIONS

Material	: Wooden Melamine.
Wood Style	: Panel
Panel Type	: Melamine veneering, High quality steel tube
Size	: 120*60*75cm
Color	: Maple

14) OFFICE TABLE

TECHNICAL SPECIFICATIONS

Material	: MFC (Melamine finished chip board) Wooden
Wood Style	: Panel
Panel Type	: Melamine
Top thickness	: 27mm
Size	: W1600*D750*H730
Accessories	: Removable cabinet, computer host rack

15) CHAIRS

WHITE DISPLAY BOARD

TECHNICAL SPECIFICATION

- ❖ White ceramic surface for dry wipe markers
- ❖ Ceramic enameled steel surface

- ❖ Scratch resistant, no ghosting
- ❖ Framed in double sided curved Astra section to give good strength
- ❖ CHROME PLATED plastic corners-good aesthetics
- ❖ Chrome plated metal corner brackets for easy fixing on the wall in landscape or portrait
- ❖ Fixing screws and anchor plugs provided
- ❖ Dimensions 600 x 1200 in mm